




Front

Rear

**① Main Board****DF51**

Side Lock
Pitch: 2.0mm
Rated Current:
3.0A Max.
UL/C-UL Certified

② Branch Connection**DF51**

Center Lock
Pitch: 2.0mm
Rated Current:
3.0A Max.
UL/C-UL Certified

③ Sub Board**KW30**

Center Lock
Pitch: 1.0mm
Rated Current:
3.0A Max.

④ Service Plug**EM30MSD**

*IPX8:
Rated Current:
200A Max.
IPX8* Water Proof
In 2m water depth
for 14 days in
mated condition
UL/TÜV Certified

⑤ Touch Panel**FH62/FH72**

One Action Lock
Pitch: 0.25/0.3mm

⑥ LED Display**DF80**

Vertical
Pitch: 0.5mm
Height: 1.72mm
Depth: 5.1mm

DF81

Horizontal
Pitch: 0.4mm
Height: 0.9mm
Depth: 2.75mm

⑦ RFID**MS-156C**

Coaxial Switch
Height: 1.35mm
Frequency:
0 to 11GHz

U.FL

Coaxial Connector
Mated Height:
1.9-2.4mm
Frequency: 0 to 18GHz Max.

⑧ Image Processing Board**FH55**

Front Flip
Pitch: 0.4/0.5mm
Height: 1.5mm
Transmission Speed: 16Gbps

FH63S

One Action Lock
Pitch: 0.5mm

FH67

One Action Lock
Vertical
Pitch: 0.5mm

⑨ In-Line Connection**DF63W**

Rated Current:
14A Max.
Water Proof

DF62W

Rated Current: 5A Max.
Water Proof
UL/C-UL Certified

⑩⑪ Power Module**DF60**


Pitch: 10.16mm
Rated Current: 65A Max.
UL/C-UL/TÜV Certified

**FX30B**

Misalignment Absorption
Pitch: 3.81mm
Rated Current: 25A Max.
UL/TÜV Certified



Front



① Main Board



DF51

Side Lock
Pitch: 2.0mm
Rated Current: 3.0A Max.
UL/C-UL Certified

④ Power Supply



HR41

Weather-Resistant
Waterproof
Surge Protection
(15kV)

⑥ LED Display



DF80

Vertical
Pitch: 0.5mm
Height: 1.72mm
Depth: 5.1mm

⑧ Image Processing Board



FH55

Front Flip
Pitch: 0.4/0.5mm
Height: 1.5mm
Transmission Speed: 16Gbps

② Branch Connection



DF51K

Center Lock
Pitch: 2.0mm
Rated Current: 3.0A Max.
UL/C-UL Certified

⑤ Touch Panel



LF

Small and Robust
Waterproof
Bayonet Lock
Shielding

HR30

Plastic Waterproof
Small Light Weight
Push-Pull Lock

⑦ RFID



DF81

Horizontal
Pitch: 0.4mm
Height: 0.9mm
Depth: 2.75mm

⑨ In-Line Connection



FH63S

One Action Lock
Pitch: 0.5mm

③ Sub Board



DF51B: In-Line Branch

Pitch: 2.0mm
Rated Current: 3.0A Max.
UL/C-UL Certified

⑥ LED Display



FH62/FH72

One Action Lock
Pitch: 0.25/0.3mm

⑧ Image Processing Board



MS-156C

Coaxial Switch
Height: 1.35mm
Frequency: 0 to 11GHz

⑩ In-Line Connection



FH67

One Action Lock
Vertical
Pitch: 0.5mm

④ Power Supply



KW30

Center Lock
Pitch: 1.0mm
Rated Current: 3.0A Max.

⑦ RFID



U.FL

Coaxial Connector
Mated Height: 1.9-2.4mm
Frequency: 0 to 18GHz Max.