

1. Interface Connection(Wire-to-Board)

Robust
125°C

ZE05

Rated Current: 2A
(All Pins Power Supply)
No. of Pos.: 2-24
AWG: 20-26




2. Interface Connection (High Speed Wire-to-Board)

Noise Resistant
105°C

GT43

Compact,
One Step Crimping
Frequency: 3GHz
Coaxial Cable: 1.5D



High Speed
105°C

GT32

Transmission Rate:
4pos.: USB2.0, LVDS Equivalent
10pos.: USB3.2 Gen.1 Equivalent
19pos.: HDMI 1.4a Type E Equivalent
AWG: 24-28
Cable Type: Twist



USB Type-C
105°C

AU1

USB 3.2 Gen2 (10Gbps),
Display Port 1.4, HDMI
Rated Current: 5A Max.
Compliant with USCAR-2 and
USCAR-30 standards



3. Internal Connection (Floating Board-to-Board, Board-to-Board(FPC))

Floating Design
125°C

BM54


Compact
Pitch: 0.4mm
Stacking Height:
3.0-4.5mm



125°C

DF40T


Low Profile,
Narrow Pitch: 0.4mm
Stacking Height: 1.5-7.0mm
1.5 (Shielded Type: DF40GT)



105°C

DF12N

Space-saving Design
Pitch : 0.5mm
Stacking Height : 3-5mm



4. Internal Connection (Coaxial)

105°C

POK15

Wire-to-Board
Mated Height : 14mm
V.S.W.R. :
1.5 Max. (0 to 3GHz)



105°C

POK16

Board-to-Board
Mated Height :
7.4mm
V.S.W.R. :
1.5 Max. (0 to 3GHz)



105°C

POK19

Board-to-Board,
Wire-to-Board
Mated Height : 9, 12mm
V.S.W.R. :
1.5 Max. (0 to 6GHz)



105°C

POK22

Floating Design
Mated Height :
16.45mm
V.S.W.R. :
1.49 Max. (0 to 6GHz)



4. Internal Connection (FPC/FFC, Wire-to-Board)

125°C

FH75/FH75M FH

Two-point Contact
Pitch: 0.5/0.4mm
Height: 2.0mm
FH75M: 100pos.



Best Selling

125°C

FH52K FH

Pitch: 0.5/1.0mm
Height: 2.0mm



Top/Bottom Contact

125°C

FH79 FH

Pitch: 0.3mm.
Height: 1.2mm




One Action

105°C

FH63S/FH67 FH

Pitch: 0.5mm
Height: 2.8, 5.2mm



Top/Bottom Contact

125°C

FH69 FH

Independent
Two-Point Contact
Pitch: 0.5mm
Height: 2.3mm



125°C

FH65 FH

Low Profile,
Space-saving Design
Pitch : 0.5mm
Height : 1.2mm



125°C

GT50

Rated Current:
1.5A (6-16pos.)
2.0A (2,4pos.)
No. of Pos.: 2-16
AWG: 28



125°C

KM32A

Rated Current: 5A
No. of Pos.: 2-10
AWG: 20

